



# FLECK 5812 CONTROL VALVE

HIGH PERFORMANCE FLEXIBLE 1-1/4" VALVE



## FEATURES/BENEFITS

Fiber-reinforced polymer valve body for superior strength and durability, non-corrosive, and UV-resistant

Continuous service flow rate of 45 GPM with a backwash of 35 GPM

Backwash capability accommodates softener tanks up to 24" and filters up to 24" in diameter

Fully adjustable 3- or 5-cycle control for efficient and reliable water treatment system

Time-tested, hydraulically-balanced piston for service and regeneration

Optical sensor for precision cycle positioning

Soft water refill for a cleaner brine tank

Designed with double backwash for reduced hardness leakage

Diagnostics for historical valve performance

Programming stored in memory and will not be lost due to power outages

## OPTIONS

Filter or softener control valves

Downflow co-current or upflow counter-current regeneration

Plumbing connections in 3/4" to 1-1/4" NPT, BSP, and sweat

Fiber-reinforced polymer high-flow bypass valve

Variable reserve for increased efficiency

Programmable regeneration types for increased flexibility

Two color bezel options of black or blue

**XTR2-** Premium touch screen LCD display with two programmable relay outputs for both normally opened and normally closed contacts

**SXT-** Large LCD display and user-selectable time clock or metered function; usable for filtration and softener systems

TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 44 for Water Softener Performance.

TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 372 for Lead Free Compliance.



UL recognized to the 979

TESTED EMC and Low Voltage Directive

Restriction of Hazardous Substance Compliant

## VALVE SPECIFICATIONS

|                |                                       |
|----------------|---------------------------------------|
| Valve Material | Fiber-reinforced polymer              |
| Inlet/Outlet   | 3/4", 1", or 1-1/4" NPT/<br>BSP/Sweat |
| Cycles         | 5                                     |

## FLOW RATES (50 PSI INLET) – VALVE ALONE - 2.5" BASE

| Piston                         | Downflow                          | Upflow                            | Filter                            |
|--------------------------------|-----------------------------------|-----------------------------------|-----------------------------------|
| Continuous<br>(15 psi drop)    | 43 GPM<br>9.9 m <sup>3</sup> /hr  | 39 GPM<br>8.9 m <sup>3</sup> /hr  | 37 GPM<br>8.4 m <sup>3</sup> /hr  |
| Peak<br>(25 psi drop)          | 56 GPM<br>12.7 m <sup>3</sup> /hr | 51 GPM<br>11.9 m <sup>3</sup> /hr | 47 GPM<br>10.7 m <sup>3</sup> /hr |
| Cv<br>(flow at 1 psi drop)     | 11.2                              | 10.1                              | 9.4                               |
| Max. Backwash<br>(25 psi drop) | 33 GPM<br>7.5 m <sup>3</sup> /hr  | 36 GPM<br>8.1 m <sup>3</sup> /hr  | 45 GPM<br>9.9 m <sup>3</sup> /hr  |

## FLOW RATES (50 PSI INLET) – VALVE ALONE - 4" BASE

| Piston                         | Downflow                          | Upflow                            | Filter                            |
|--------------------------------|-----------------------------------|-----------------------------------|-----------------------------------|
| Continuous<br>(15 psi drop)    | 45 GPM<br>10.3 m <sup>3</sup> /hr | 40 GPM<br>9.1 m <sup>3</sup> /hr  | 38 GPM<br>8.7 m <sup>3</sup> /hr  |
| Peak<br>(25 psi drop)          | 59 GPM<br>13.3 m <sup>3</sup> /hr | 52 GPM<br>11.7 m <sup>3</sup> /hr | 50 GPM<br>11.3 m <sup>3</sup> /hr |
| Cv<br>(flow at 1 psi drop)     | 11.7                              | 10.3                              | 9.9                               |
| Max. Backwash<br>(25 psi drop) | 34 GPM<br>7.8 m <sup>3</sup> /hr  | 36 GPM<br>8.2 m <sup>3</sup> /hr  | 45 GPM<br>10.2 m <sup>3</sup> /hr |

## REGENERATION

|                   |                   |
|-------------------|-------------------|
| Downflow/Upflow   | Both              |
| Adjustable Cycles | Yes               |
| Time Available    |                   |
| SXT:              | 0 - 199 min/cycle |
| XTR2:             | 0 - 240 min/cycle |

## METER INFORMATION

|                      |                                                    |
|----------------------|----------------------------------------------------|
| Meter Accuracy       |                                                    |
| 1-1/4" Turbine:      | 2 - 40 GPM ± 5%<br>[0.45 - 9 m <sup>3</sup> /h]    |
| Meter Capacity Range |                                                    |
| SXT:                 | 1 - 999,900 gal<br>[0 - 3,785 m <sup>3</sup> ]     |
| XTR2:                | 1 - 9,999,999 gal<br>[0 - 378,541 m <sup>3</sup> ] |

## DIMENSIONS

|                            |                                                         |
|----------------------------|---------------------------------------------------------|
| Distributor Pilot          | 1.05" O.D. (26.7 mm)<br>32 mm I.D.<br>1" I.D. (25.4 mm) |
| Drain Line                 | 1.5" NPTF<br>Quick-Connect                              |
| Brine Valve                |                                                         |
| 1600:                      | 3/8"                                                    |
| Injector System            | 1610                                                    |
| Mounting Base              | 2.5" - 8 NPSM<br>4" - NPSM                              |
| Height from<br>Top of Tank | 12" (305 mm)                                            |
| Riser Height               | 1/4" Below top of tank                                  |

## TYPICAL APPLICATIONS

|                |                                                     |
|----------------|-----------------------------------------------------|
| Water Softener | 8 - 24" diameter                                    |
| Filters        | 8 - 24" diameter<br>based on 10 GPM/ft <sup>2</sup> |

## ADDITIONAL INFORMATION

|                           |                                 |
|---------------------------|---------------------------------|
| Electrical Rating         | 12 Volts DC                     |
| Estimated Shipping Weight | 12 lbs                          |
| Pressure                  |                                 |
| Hydrostatic:              | 300 psi<br>(20 bar)             |
| Working:                  | 20 - 125 psi<br>(1.4 - 8.5 bar) |
| Temperature               |                                 |
| Cold Water Valve:         | 34 - 110°F (1 - 43°C)           |



## PENTAIR WATER QUALITY SYSTEMS

5730 A A A 53209  
: 262.238.4400 : 262.238.4404  
A CA A C  
C CA : 800.279.9404 -  
2015 I I I I I C. A I

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.  
4004319 REV A MR15